ZUZZ PINE GLENN STREET AND UTILITY IMPROVEMENTS

RELEASED FOR BIDDING

CITY OF STURGIS PUBLIC WORKS DEPARTMENT STURGIS, SOUTH DAKOTA CLIENT PROJECT # PINEGLENN

UTILITY AND EMERGENCY TELEPHONE NUMBERS

EMERGENCY:	911
SOUTH DAKOTA ONE CALL	1-(800) 781-7474
BLACK HILLS ENERGY	(888) 890-5554
CENTURYLINK	(605) 394-4720
MIDCO	(605) 787-3371
MDU	(605) 642-2654
VAST BROADBAND	(605) 721-2000
CITY OF STURGIS WATER	(605) 347-3916
CITY OF STURGIS WASTEWATER	(605) 347-3916
CITY OF STURGIS PUBLIC WORKS	(605) 347-3916

OWNER CONTACT INFORMATION

RICK J. BUSH, CPWP-M DIRECTOR OF PUBLIC WORKS OFFICE (605) 347-3916

ENGINEER CONTACT INFORMATION

THEODORE F. SCHULTZ - PE FOTH INFRASTRUCTURE & ENVIRONMENT, LLC 510 NINTH STREET, SUITE 200 RAPID CITY, SOUTH DAKOTA 57701 (605) 381-0433

PROPERTY ADDRESS


NEAR INTERSECTION OF PINE GLENN DR./DOLAN CREEK RD. IN STURGIS, SOUTH DAKOTA 57785


UTILITY NOTES

WHERE PUBLIC UTILITY FIXTURES ARE SHOWN AS EXISTING ON THE PLANS OR ENCOUNTERED WITHIN THE CONSTRUCTION AREA, IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO NOTIFY THE OWNERS OF THOSE UTILITIES PRIOR TO THE BEGINNING OF ANY CONSTRUCTION. THE CONTRACTOR SHALL AFFORD ACCESS TO THESE FACILITIES FOR NECESSARY MODIFICATION OF SERVICES. UNDERGROUND FACILITIES, STRUCTURES AND UTILITIES HAVE BEEN PLOTTED FROM AVAILABLE SURVEYS AND RECORDS, AND THEREFORE THEIR LOCATIONS MUST BE CONSIDERED APPROXIMATE ONLY. IT IS POSSIBLE THERE MAY BE OTHERS, THE EXISTENCE OF WHICH PRESENTLY NOT KNOWN OR SHOWN. IT IS THE CONTRACTOR'S RESPONSIBLITY TO DETERMINE THEIR EXISTENCE AND EXACT LOCATION AND TO AVOID DAMAGE THERETO. NO CLAIMS FOR ADDITIONAL COMPENSATION WILL BE ALLOWED TO THE CONTRACTOR FOR ANY INTERFERENCE OR DELAY CAUSED BY SUCH WORK.

THE CONTRACTOR IS REQUIRED TO UTILIZE THE UTILITY ONE-CALL SERVICE AT (800) 781-7474 AT LEAST 48 HOURS PRIOR TO EXCAVATING ANYWHERE ON THE PROJECT. THE CONTRACTOR MUST ALSO CONTACT THE AIRPORT AND THE FAA AT LEAST 48 HOURS IN ADVANCE FOR LOCATES.

UTILITY CONFLICTS DISCOVERED DURING CONSTRUCTION WILL BE ADDRESSED AT THE TIME OF





	INDEX OF SHEETS
NO.	DESCRIPTION
G0.00	TITLE SHEET
G0.01	LEGEND
G0.02	GENERAL PROJECT NOTES
G0.03-G0.04	STORMWATER POLLUTION PREVENTION PLAN
C0.01	TYPICAL SECTION
C0.02	ALIGNMENT DIAGRAM
C1.01	TRAFFIC CONTROL
C1.02	EROSION CONTROL PLAN
C1.03	GRADING PLAN
C1.04	SITE PLAN
C1.05-C1.07	SANITARY SEWER PLAN PROFILE
C1.08-C1.09	ROADWAY PLAN PROFILE
C1.10-C1.13	WATER MAIN PLAN PROFILE
C3.01-C3.11	CROSS SECTIONS
C5.01-C5.04	CONSTRUCTION DETAILS
	Automatical Control of the Control o
	- The state of the
	200 1 10
) 1.000





Section Sect	CABLE TV				STORM SEWER				DRIVEWAY		_		ROADWAY	EXISTING	DEMO/REMOVAL	PROPOSED
March Marc	CABLE TELEVISION - BURIED -	EXISTING	DEMO/REMOVAL	PROPOSED	STORM SEWER - SERVICE LATERAL	EXISTING	DEMO/REMOVAL	PROPOSED	DRIVEWAY - CONCRETE PATTERN	EXISTING	DEMO/REMOVAL	PROPOSED		PATTERN: AR-CONC		
March 1999 1						(ST) [7]	(a) []	(ST)					DOADWAY CUIDB BACY	3CALE: 0.70		-17 - 17 - 07
Part					STORM SEWER (PROFILE)				EASEMENT							
The content of the				•	Section Application of Print Application				EACEMENT - DEDMANENT	EXISTING	DEMO/REMOVAL	PROPOSED				
March Marc	CABLE TELEVISION - PEDESTAL	8	\triangledown	lacktriangle	TELEPHONE	EXISTING	DEMO/REMOVAL	PROPOSED								
Color Colo	ELECTRIC				TELEPHONE - JUNCTION BOX	-			EROSION CONTROL					AVEL		
The control	ELECTRICAL - FOUIPMENT													polypodyddiaddiaddia	***************************************	GRAVEL PROPUSED
March Marc				FIRE ALARM BOX		V	v ·	▽	EROSION CONTROL - FILTE WATTLE OR DITCH CHECK GEN	R BAG			The second second second second			
MATERIAL PROPERTY						(T)	Õ	Θ	ERO BA							
MINISTRATION Company		\bowtie	\boxtimes	\boxtimes				11								
STATE STAT	ELECTRICAL - LIGHT FIXTURE	UTLITY & LIGHT POLE		UTILITY & LIGHT POLE	WATER SERVICE	EVICTIVA	DEMO(DEMOVA)	PROPOSER	- EROSION CONTROL -			500000				
March Conference	ELECTRICAL - LIGHT HANDHOLE -	Ϋ́	. 4	Y	WATER - APPURTENANCE	(W)			CONSTRUCTION ENTRANCE			March 1				
March Marc	ELECTRICAL - OVERHEAD CABLE -				WATER - PIPE CENTERLINE				EROSION CONTROL - CONSTRUCTION ENTRANCE					EXISTING	DEMO/REMOVAL	PROPOSED
Courte Court Cou	ELECTRICAL - PEDESTAL	V	₹	\blacksquare	WATER - HYDRANT	V	$\boldsymbol{\beta}$	V								
March Marc	ELECTRICAL - POLE	TILITY POLE WITH TRANSFORMER	UTILITY POLE WITH TRANSFORMER		WATER-PIPE				WETLAND DISTURBED AREA							
Married Marr	ELECTRICAL - TOWER	\boxtimes	\boxtimes	\boxtimes	WATER - STRUCTURE	(W) (W) []	$\otimes \otimes \Box \Box$	₩ □			SCALE 12.		SITE-BUILDING OUTLINE			
Marie Mari	ELECTRICAL - UNDERGROUND CABLE -				WATER-STRUCTURE-PATTERN	VALVE CURB	VALVE CURB	VALVE CURB	RESTORATION TYPE 1		RESTORATION TYPE PATTERN: TRIANG SCAU: 12.	7 7 7 7 7 7 7				
WATER CONTROL WATER CONTRO	ELECTRICAL - UNDERGROUND DUCT -				WATER-VALVE		>1 °E _W		PI ANTINGS				SITE-BUILDING RUINS	-		-
Transport	ELECTRICAL - HANDHOLE -		-		WATER-WELL	♦ W		◆ w	LANTINOS	CEXISTING!	DEMO/REMOVAL	CPROPOSED	CITE CONCRETE DATTERN			
## CONTROL CO	ELECTRICAL - UNDERGROUND STRUCTURE				WATER-PROFILE		======			₩ ₩	8 C					PATTER A CONCORDANCE)
MINISCELLANDERS 15	FIBER OPTIC				TELECOMMUNICATIONS -				_ {	7			}			Kalta 10 des
MINISTERLANDOR DITUITY TEACH MATERIAL MATERI		EXISTING	DEMO/REMOVAL	PROPOSED	TELECOM - MISCELLANFOUS	EXISTING	DEMO/REMOVAL	PROPOSED				~ ~~~~~	3			Tracing the state of the state
Microsoft Language Temporary Tempora		FO	F0	F0					The same to the same of the sa		س	سع				Section of the sectio
VELLIANGE CHIEF CONTROL CONTR		, 0							PLANTING-SHRUB	ພ	ພ	ພ	SITE-FENCE-BARBED WIRE		-	
Manual Control	MISCELLANEOUS UTILITY	EXISTING	DEMO/REMOVAL	PROPOSED	CONTOURS AND TINN				PLANTING-STUMP		基		SITE-FENCE-CHAIN LINK		:	
MEDICAGE PARTY 1	MISCELLANEOUS UTILITY - OVERHEAD CABLE -						EXISTING	PROPOSED	_	CONF. DECD.	• •	CONF. DECO.	SITE-FENCE-FIELD			
SCHOOL-SHEET BETTER AND ALL STREAMS AND LAKES SCHOOL-SHEET BETTER AND STREAMS AND LAKES SCHOOL-SHEET BETTER A	MISCELLANEOUS UTILITY - GUY ANCHOR	←		€			And the second s			0 10 0 12			SITE-FENCE-WOOD			
MESILANGUARISHTANIANOL GO CONTROL SECULARISHTANIANOL GO CONTROL SECULARISHTANIANOL GO CONTROL SECULARISHTANIANOL GO CONTROL C		П						(695)						⊸ 6∕ ∕9—	⊸ ⁄ >	⊸ ⁄ ⋄
MINISTERIA MARCINE MELE ADMINISTRATION CONTROL MELE ADMINISTRATION CONTR		,		,					PROPERTY	EVICTING	DEMO/BEMOVAL	PROPOSED	SITE-GATE	⊸ 	⊸ =	⊸
MATURAL GAS NOTIFICAL CONTROL STATEMENT AND A STATEMENT AND	MISCELLANEOUS UTILITY -					ATEDSHED			PROPERTY - LOTLINE		DEMO/REMOVAL			LIGHT - LIGHT -	LIGHT - LIGHT -	LIGHT- LIGHT-
MACHINA CLAS DETINES DETINES	MISCELLANEOUS UTILITY - MANHOLE	(MH) [I		MH \square		ATENOTIED			PROPERTY-PARCEL	=::=::=		=::=::=	SITE-LIGHT	₩ O-4	■ O-4	₩ 0≪
MOTURAL GAS CONTROL SUMMER SUMME	MISCELL ANEOLIS LITTLITY - POLE								PROPERTY - PROPERTY				SITE-MAILBOX	MB		
NUMBER CONTINUENCE CONTINU		-		-					PROPERTY - QUARTER SECTION				SITE - SEPTIC TANK			
MINISTRA, CALL PRISONAL PRISON	IN I UNAL DAS	EXISTING	DEMO/REMOVAL	PROPOSED		EXISTING	DEMO/REMOVAL						SITE-SIGN	₽	₽	₽
SOURCE AND CONTROL FROM CONTROL	NATURAL GAS - APPURTENANCE	PROBE G METER	⊕ ⊚	↔ ७	CONTROL - GENERAL			♥ _{CP}	PROPERTY - RIGHT OF WAY MARKER	ROW			DDOE!! E			
NOTIVE DE CHIEF PER CONTRUIT PE	NATURAL GAS - PIPE CENTERLINE (PLAN) —		======		CONTROL - IRON ROD								PRUFILE	EXISTING	DEMO/REMOVAL	PROPOSED
DATE OF THE REPORT OF THE REPO								***					C-PROF-DTCH		•	
DRAINAGE Committee Contribution Committee	NATURAL GAS - PIPE MAIN				CONTROL - REBAR			O _{RB}	TOPOGRAPHY - GENE				C-PROF-GRAD	CAN THE SEASON SAND	궽	
MANUAL CONTROL DE DITTING DEMONSTRATION DE DEMONSTRATION					DDAINAGE				GEOTECHNICAL - SOILS BOUNDARY				OTHOR GIVE		1	
SANITARY SEWER DOISTING DOIST					DRAINAGE	EXISTING	DEMO/REMOVAL	PROPOSED	GEOTECHNICAL - SOIL BORING	◆BORING #	◆BORING #	◆BORING #				
ENTRATE EMBIR - ABACONDS ENTRATE EMBIR - ABACONS ENTRATE EMBIR - ABACONS		(6)	(10)	•	DRAINAGE - DITCH - CENTERLINE				RIVERS AND STREAM	S AND LAKES						
SAME SERVICE SERVICE AND SERVICE SERVI	SANITAKY SEWER	EXISTING	DEMO/REMOVAL	PROPOSED					DIVED OR STREAM FROM SELECTION		DEMO/REMOVAL					- National Property
SANTARY SERVER, CHRISTORY OF THE SHAWN TO	SANITARY SEWER - ABANDONED —		- I I I I I I I I I I I I I I I I I I I						KIVER OR STREAM - EDGE OF WATER	<u></u>						were of scattered of the news
DENINGE TRACEOUR ASPER LETS TATION DENINGE ASSET POST DESCRIPTION DENINGE ASSET POST DESCRIP	SANITARY SEWER - PIPE CENTERLINE (PLAN) -			-												(Augusta
SANTARY SERVE LITE STATION SANTARY SERVE SERVICE LATERAL SANTARY SERVICE LATERAL SANTARY SERVE SERVICE LATERAL SANTARY SERVE SERVICE LATERAL SANTARY SERVE SERVICE LATERAL SANTARY SERVE SERVICE LATERAL SANTARY SERVICE LATERAL SANTARY SERVICE LAT	SANITARY SEWER - CLEANOUT	0	⊙	0		— TD —	— TD —	TD	ROADWAY	EXISTING	DEMO/REMOVAL	PROPOSED	GRADE ELEVATION (PROFILE)			# 6.0 #18.0
SANTARY SEVERFOR VALL SANTARY SEVERFOR COLE -ASAN - MOST DEVELOPMENT TA DEMANGEASAN - POST DEVLOPMENT - TAME OF CONCENTRATION DEMANGEASAN - FOR DEVLOPMENT - TAME OF CONCENTRATION SANTARY SEVERFOR COLE DEMANGEASAN - FOR DEVLOPMENT - TAME OF CONCENTRATION RAPPOVED BY TORM SEVER FOR COLE STORM SEVER FOR COLD HASIN STORM SEVER FOR CO	SANITARY SEWER - FORCEMAIN —		—— FM ——						ROADWAY - ASPHALT FOGE				.mvacessagsprong.co-000000 N 00000007			841 835
SANTARY SEVER - SERVED - SERVE	SANITARY SEWER - LIFT STATION	LE	21	LE	DRAINAGE - ARROW	~~ ~		~~ ~								
SANTARY SEWER-STRUCTURE SANTARY SEWER-TRIANCTURE SANTARY SEWER-TRIANCTURE ADMONDS SANTARY SEWER-TRIANCTURE ADMONDS SANTARY SEWER-TRIANCTURE ADMONDS SANTARY SEWER-TRIANCE SANTARY SEWER-PROOFEE DRIANCE-BASIN-PRE DEVECTORMENT TIME OF CONCENTRATION BOADWAY-ASPHALT SHOULDER ROADWAY-CONTRIBURE ROADWAY-CONTRIBURE STORM SEWER-ADMONDS STORM SEWER-ADMONDS STORM SEWER-ADMONDS STORM SEWER-ADMONDS STORM SEWER-PRE CENTERLING PLAN STORM SEWER-DECED STORM SEWER-ADMONDS STORM SEWER-CALVERT STORM SEWER-CALVERT STORM SEWER-DECED STORM SEW	SANITARY SEWER - PIPE WALL -											AGGREGATE PAVEMENT				
SANTARY SEVER PROPULE) LENGTHOLA MATERIAL © GRADE STORM SEWER STORM SEWER - BANDONED STORM SEWER - PIPE CENTRULINE (PLAN) STORM SEWER - PIPE STORM SEWER - STRUCTURE ABANDONED STORM SEWER - PIPE STORM SEWER - STRUCTURE AND LITHUITY IMPROVEMENTS STORM SEWER - PIPE STORM SEWER -	SANITARY SEWER - SERVICE LATERAL -	^	<i></i>	0 -					•							
SANTARY SEWER (PROFILE) SANTARY SEWER (PROFILE) LENGTHOLA MATERIAL GRADE STORM SEWER STORM SEWER DIVEWAY DIRVEWAY DIRVEWAY DIRVEWAY-ASPHALT ENDING DIRVEWAY-ASPHALT ENDING DIRVEWAY-ASPHALT ENDING DIRVEWAY-ASPHALT ENDING DIRVEWAY-CONCRETE EDGE DIRVEWAY-CONCRETE		(SA)	(sa) []	(SA)					•							
SANTARY SEWER (PROFILE) LENGTH-OIA: MATERIAL © GRADE STORM SEWER CHORAN-ASPHALT EDGE DRIVEWAY STORM SEWER DRIVEWAY STORM SEWER - ABANDONED STORM SEWER - ABANDONED STORM SEWER - ABANDONED STORM SEWER - PIPE CENTERLINE (PLAN) DRIVEWAY - ASPHALT EDGE DRIVEWAY - ASPHALT ENTERLINE DRIVEWAY - ASPHALT PATTERN STORM SEWER - PIPE DRIVEWAY - ASPHALT PATTERN DRIVEWAY - ASPHAL		A STREET STREET, STREE			DRAINAGE - BASIN - PRE DEVELOPMENT 1.											
DRIVEWAY STORM SEWER STORM SEVER - ABANDONED STORM SEVER - PIPE DRIVEWAY - ASPHALT EXITERINE DRIVEWAY - ASPHALT EXITERINE DRIVEWAY - ASPHALT PATTERN DRIVEWA	SANITARY SEWER - TUNNEL -			-		IME OF CONCENTRATION			ROADWAY - ASPHALT SHOULDER							
STORM SEWER - PIPE CHETRILINE (PLAN) STORM SEWER - PIPE CHETRILINE (PLAN) STORM SEWER - PIPE STORM SEWER - PIPE STORM SEWER - PIPE STORM SEWER - PIPE DRIVEWAY - ASPHALT PATTERN STORM SEWER - PIPE DRIVEWAY - SHALL PATTERN DRIVEWAY - ASPHALT PATTERN DRIVEWAY - SHALL PATTERN DRIVEWAY - ASPHALT PATTERN DRIVEWAY - SHALL PATTERN DRIVEWAY -			======						ROADWAY - TRAFFIC CONTROL BARREL	PI		O _{PI}				APPROVED BY:
STORM SEWER - PIPE CHETRILINE (PLAN) STORM SEWER - PIPE CHETRILINE (PLAN) STORM SEWER - PIPE STORM SEWER - PIPE STORM SEWER - PIPE STORM SEWER - PIPE DRIVEWAY - ASPHALT PATTERN STORM SEWER - PIPE DRIVEWAY - SHALL PATTERN DRIVEWAY - ASPHALT PATTERN DRIVEWAY - SHALL PATTERN DRIVEWAY - ASPHALT PATTERN DRIVEWAY - SHALL PATTERN DRIVEWAY -					DRIVEWAY				ROADWAY - CENTERLINE	0		0				REPORT WAS RALL AND THAT I AM
STORM SEWER - PIPE CHETRILINE (PLAN) STORM SEWER - PIPE CHETRILINE (PLAN) STORM SEWER - PIPE STORM SEWER - PIPE STORM SEWER - PIPE STORM SEWER - PIPE DRIVEWAY - ASPHALT PATTERN STORM SEWER - PIPE DRIVEWAY - SHALL PATTERN DRIVEWAY - ASPHALT PATTERN DRIVEWAY - SHALL PATTERN DRIVEWAY - ASPHALT PATTERN DRIVEWAY - SHALL PATTERN DRIVEWAY -	O I ORIVI SEVYER	EXISTING	DEMO/REMOVAL	PROPOSED	DRIVEWAY - ASPHALT EDGE	EXISTING	DEMO/REMOVAL	PROPOSED	. ROADWAY - CONCRETE EDGE							
STORM SEWER-PIPE CENTERLINE (PLAN) STORM SEWER-CULVERT STORM SEWER-INLET OR CATCH BASIN STORM SEWER-PIPE DRIVEWAY-CONCRETE EDGE DRIVEWAY-CONCRETE EDGE DRIVEWAY-GRAVEL EDGE DRIVEWAY-GRAVEL EDGE DRIVEWAY-ASPHALT PATTERN DRIVEW	STORM SEWER - ABANDONED -		-													7113
STORM SEWER-CULVERT STORM SEWER-INLET OR CATCH BASIN STORM SEWER-PIPE STORM SEWER-PIPE DRIVEWAY-ASPHALT PATTERN DRIVEW	STORM SEWER - PIPE CENTERLINE (PLAN)				DRIVEWAY - CONCRETE EDGE	:			ROADWAY - CONCRETE PATTERN			ROAD (BRICK) FATTERN BRICK				SIGNATURE SCHOOL
STORM SEWER-PIPE STORM SEWER-PIPE DRIVEWAY-ASPHALT PATTERN DRIVEWAY-ASPHALT PATTERN DRIVEWAY-ASPHALT PATTERN DRIVEWAY-ASPHALT PATTERN CIVIL STANDARDS CIVIL STANDARDS	STORM SEWER - CULVERT -) ====		DRIVEWAY - GRAVEL EDGE			-		CONCRETE PAVEMENT	品介 生生	XAE 15				THEOLORE F. SONNIST
NO. PINE GIENN FOTH PROJECT NO. 215100.00 NO DATE BY REVISION DESCRIPTION DINE CLEAN STREET AND LITH TY LARDOVERAENTS CIVIL STANDARDS	STORM SEWER - INLET OR CATCH BASIN				DRIVEWAY - ASPHALT PATTERN			***************************************		PATTERN: SOLID						Eld a tille
NO. PINE GIENN FOTH PROJECT NO: 21S100.00 NO DATE BY REVISION DESCRIPTION	STORM SEWER - PIPE —						:#C									7/28/2022mm
NO: PINE GLENN FOTH PROJECT NO: 21S100.00 KRM CHECKED BY: TFS DRAWN BY: MLH CAD DATE 5/2/2022 8:25:19 AM CAD DATE 5/2/2022 8:25:19 AM PINE GLENN STREET AND UTILITY IMPROVEMENTS SYMBOLOGY AND ABBREVIATIONS CIVIL STANDARDS SYMBOLOGY AND ABBREVIATIONS			Transfer		BENIGION DECORPTION								W. W. O. T. L. D T. T.			1
CAD DATE 5/2/2022 8:25:19 AM 2 SYMBULUGY AND ABBREVIATIONS			- 4	IE BY	REVISION DESCRIPTION		√ F_4		PINE GLENN STREET	AND UTILITY I	MPROVEME	INTS C	IVIL STANDARDS		10	
			2		*	—— I →						I S	AMIROFORA WND W	RRKENIALIO	42	

GENERAL PROJECT NOTES

CONSTRUCTION SEQUENCE

- A PRECONSTRUCTION MEETING MUST BE HELD BEFORE ANY CONSTRUCTION ACTIVITIES TAKE PLACE.
- THE CONTRACTOR IS REQUIRED TO NOTIFY THE SD DANR OF ALL OFFSITE DISPOSAL LOCATIONS, INCLUDING ESTIMATED QUANTITIES, PRIOR TO EXPORTING MATERIAL FROM THE SITE.
- ONCE CONSTRUCTION BEGINS CONTINUOUS PROGRESS MUST BE MADE UNTIL SUBSTANTIAL COMPLETION HAS BEEN
- CONTRACTOR SHALL INSTALL EROSION CONTROLS AT LOCATIONS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER BEFORE ANY GRADING ACTIVITIES TAKE PLACE
- CONTRACTOR IS REQUIRED TO PROVIDE A TRAFFIC CONTROL PLAN PRIOR TO CONSTRUCTION THAT FOLLOWS THE REQUIREMENTS OF THE TRAFFIC CONTROL PLAN SHEET(S). INSTALL ALL TRAFFIC CONTROL AND PROVIDE ACCESS AREAS AS
- TRAFFIC WILL BE MAINTAINED AT ALL TIMES.
- CONTRACTOR SHALL STRIP / SALVAGE, STOCKPILE PRIOR TO CONSTRUCTION AND RESPREAD TO EXISTING TOPSOIL DEPTHS.
- CONTRACTOR SHALL INSTALL DRIVEWAY CULVERTS AND RE-INSTALL ANY STORM SEWER DISTURBED DURING
- RESTORATION SHALL BE COMPLETED PROMPTLY FOLLOWING APPROVED PIPE INSTALLATION AND BACKFILL OPERATIONS.
- 10. EROSION CONTROL DEVICES SHALL BE REMOVED AFTER VEGETATION IS ESTABLISHED.

GENERAL NOTES

- CONTRACTOR SHALL PROVIDE TRAFFIC CONTROL PLAN TO ENGINEER PRIOR TO CONSTRUCTION FOR APPROVAL.
- ALL TRAFFIC CONTROL SHALL BE IN ACCORDANCE WITH CURRENT MUTCD STANDARDS AND SECTION 634 OF THE SOUTH DAKOTA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES, CURRENT EDITION.
- CONTRACTOR SHALL REMOVE ALL SIGNS PROTECT AND CONFIRM WITH OWNER PRIOR TO REINSTALLATION, OWNER MAY PROVIDE NEW SIGNAGE PRIOR TO INSTALLATION. ALL TRAFFIC CONTROL AND STREET SIGNS DAMAGED OR MOVED BY THE CONTRACTOR SHALL BE RESET, REPLACED OR REPAIRED WITHOUT ADDITIONAL PAYMENT.
- CONTRACTOR SHALL PROVIDE ACCESS TO TRAFFIC AT ALL TIMES. COORDINATE WITH PROPERTY OWNERS FOR ALL WORK **BLOCKING DRIVEWAYS**
- ALL MANHOLES SHALL BE ADJUSTED TO FINISHED GRADE. THIS WORK IS INCIDENTAL TO THE PROJECT UNLESS A SPECIFIC BID ITEM IS INCLUDED IN THE PROJECT MANUAL.
- THE MOST CURRENT EDITION OF THE SOUTH DAKOTA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES WITH SUPPLEMENTAL SPECIFICATIONS AND ERRATA, STANDARD PLATES AND REQUIRED PROVISIONS, SUPPLEMENTAL SPECIFICATIONS AND/OR SPECIAL PROVISIONS AS INCLUDED IN THE PROJECT MANUAL ARE HEREBY MADE A PART OF THESE SPECIFICATIONS IN ITS ENTIRETY UNLESS OTHERWISE REVISED, DELETED, OR SUPPLEMENTED HEREIN.
- THE SOUTH DAKOTA DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES WITH SUPPLEMENTAL SPECIFICATIONS AND ERRATA CAN BE DOWNLOADED FROM THE SDDOT'S WEBSITE AT http://www.sddot.com/
- SANITARY SEWER SHALL BE CONSTRUCTED ACCORDING TO THE SPECIFICATIONS AND SHALL MEET THE CITY OF STURGIS, SD AND DANK REQUIREMENTS
- WATER SPECIFICATIONS SHALL BE CONSTRUCTED ACCORDING TO THE SPECIFICATIONS AND SHALL MEET THE CITY OF STURGIS, SD AND DANR REQUIREMENTS.
- THE CONSTRUCTION LIMITS SHALL BE WITHIN THE RIGHT OF WAY AND CITY PROPERTY. THE CONTRACTOR IS RESPONSIBLE FOR ESTABLISHING A STAGING/STOCKPILE AREA FOR MATERIALS AND/ OR EQUIPMENT. MATERIAL STORAGE AND VEHICLE AND EQUIPMENT TRAFFIC SHALL BE LIMITED TO CITY PROPERTY. THE CONTRACTOR SHALL WORK WITH THE ENGINEER TO DELINEATE STORAGE AREAS. THE CONTRACTOR IS RESPONSIBLE FOR THE SECURITY AND PROTECTION OF ALL STORED MATERIALS CONSTRUCTION LIMITS SHALL BE KEPT NEAT AND ORDERLY DURING NON-WORKING HOURS. THE CONTRACTOR SHALL RECLAIM THE AREA TO THE SATISFACTION OF THE ENGINEER. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO COORDINATE WITH THE PROPERTY OWNERS RELATING TO ACCESS TO THEIR PROPERTY AND ANY SUBSEQUENT DAMAGES.
- THE CONTRACTOR WILL BE RESPONSIBLE FOR ORGANIZING THIRD PARTY ACCEPTANCE TESTS AND A BACKUP TEST IF REQUIRED. THE CITY MUST RECEIVE ALL TEST RESULTS DIRECTLY FROM THE TESTING AGENCY. ALL TESTS REQUIRED WILL BE PAID BY THE CONTRACTOR AND MEET THE APPROPRIATE TESTING REQUIREMENTS.
- DRAINAGE IS THE CONTRACTOR'S RESPONSIBILITY. CONTRACTOR SHALL BE AWARE OF EXISTING DRAINAGE CONDITIONS AND FACILITIES, AND SHALL PROVIDE FOR DRAINAGE DURING ALL PHASES OF CONSTRUCTION. DAMAGE CAUSED BY IMPROPER TEMPORARY DRAINAGE FACILITIES SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE AND TO THE SATISFACTION OF THE
- THE CONTRACTOR SHALL COOPERATE WITH AND COORDINATE HIS EFFORTS TO WORK WITH THE UTILITY COMPANIES AND THEIR CONTRACTORS. EACH BIDDER SHALL BE RESPONSIBLE PRIOR TO BID LETTING, FOR DETERMINING THE EFFECTS OF UTILITY WORK ON THE PROJECT WORK SCOPE AND SCHEDULE, AND SHALL ACCOUNT FOR ALL SUCH EFFECTS IN HIS BID. NO CONSIDERATION WILL BE GIVEN TO THE CONTRACTOR AFTER THE BID LETTING ON ACCOUNT OF UTILITY WORK DONE BY
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING WATER FOR COMPACTION OF GRANULAR MATERIALS AND TRENCH BACKFILL AS REQUIRED. THE COST OF LOADING TRANSPORTING AND APPLYING WATER SHALL BE INCIDENTAL TO THE VARIOUS ITEMS WHERE WATER IS REQUIRED. THE CONTRACTOR, MAY OBTAIN WATER FROM THE CITY.
- THE CONTRACTOR SHALL MAINTAIN THE COMPLETED SUBGRADE AND BASE COURSE. WHERE DISTURBED BY SUBSEQUENT CONSTRUCTION ACTIVITY OR ADVERSE WEATHER, THE CONTRACTOR SHALL SCARIFY, RESHAPE AND COMPACT THE MATERIAL TO REQUIRED DENSITY. ADDITIONAL PAYMENT SHALL NOT BE MADE FOR MAINTENANCE.

GENERAL PROJECT NOTES

RESTORATION NOTES

- SOIL LAYERS SHALL BE SEGREGATED DURING CONSTRUCTION ACTIVITIES. FOLLOWED BY REPLACEMENT OF SOILS IN KIND.
- 2. EROSION CONTROL MATTING WILL BE USED TO STABILIZE SLOPES WHERE CHANNELIZED FLOW IS PRESENT.

UTILITY NOTES

- CONTRACTOR IS RESPONSIBLE FOR MAINTAINING WATER AND SEWER SERVICE AT ALL TIMES DURING CONSTRUCTION. IF BYPASS PUMPING OR POTABLE WATER REPOUTING IS FOUND TO BE NECESSARY, CONTRACTOR SHALL NOTIFY OWNER AND ENGINEER. BYPASS PUMPING AND POTABLE WATER REROUTING CONSISTS OF CHANGING THE PATH OF FLOW TO ALLOW WORK TO TAKE PLACE IN THAT AREA. CONTRACTOR SHALL PROVIDE A REROUTING AND DISINFECTION PLAN TO THE ENGINEER AND OWNER FOR APPROVAL PRIOR TO WORK. BYPASS PUMPING AND WATER REROUTING SHALL BE PAID FOR ON A TIME AND MATERIALS BASIS UP TO THE BID ITEM AMOUNT.
- EXISTING WATER MAIN ABANDONMENT. AFTER SUCCESSFUL COMPLETION OF CONNECTION TO NEW WATER MAIN, EXISTING WATER MAIN SHALL AND ALL ASSOCIATED SERVICES. CURB STOP AND BOX, HYDRANTS, ETC. SHALL BE ABANDONED ACCORDING TO CITY REQUIREMENTS, ABANDONMENT SHALL BE PAID FOR AS A LUMP SUM AMOUN
- CONTRACTOR IS RESPONSIBLE AND SHALL MAINTAIN ALL DRAINAGE WITHIN THE PROJECT WORK AREA, INCLUDING RIGHT-OF-WAY ACCESS LOCATIONS DURING CONSTRUCTION.
- ALL SANITARY SEWER AND WATER MAIN SHALL BE BACKFILLED PER TRENCH CONSTRUCTION DETAILS AND AS DESIGNATED ON THE PLAN PROFILE SHEETS.
- ALL SANITARY SEWER AND WATER MAIN SHALL HAVE A CHECK DAM PLACED EVERY 250-FEET IN DISTANCE AT A MAXIMUM
- SUPPORT EXISTING UTILITIES AT CROSSINGS AS NECESSARY TO PREVENT DAMAGE OR INTERRUPTION OF SERVICE
- CONTRACTOR SHALL COORDINATE WITH THE APPLICABLE UTILITY COMPANIES AND THE CITY OF STURGIS FOR SERVICES OR UTILITIES ENCOUNTERED ON THE SITE. THIS COORDINATION SHALL BE INCIDENTAL TO THE PROJECT.
- THE INFORMATION ON THESE DRAWINGS CONCERNING THE TYPE SIZE, AND LOCATION OF UTILITIES HAS BEEN SHOWN BASED UPON THE BEST INFORMATION AVAILABLE. THE UTILITY LOCATIONS SHOWN WERE BASED ON FIELD LOCATES AND FROM OWNER'S RECORDS. THE SIZE AND LOCATION OF UNDERGROUND UTILITIES WAS NOT VERIFIED BY EXCAVATION. THE CONTRACTOR IS RESPONSIBLE FOR DETERMINING THE EXACT LOCATION OF ALL UTILITIES PRIOR TO BEGINNING CONSTRUCTION.
- WATER MAIN JOINT & FITTING RESTRAINT RESTRAINED JOINTS SHALL BE USED. ALL VALVES, FITTINGS, AND JOINTS WITHIN THE SPECIFIED RESTRAINED LENGTH SHALL BE RESTRAINED USING THE EBBA, OR APPROVED EQUAL RESTRAINING SYSTEMS. SEE SHEET N-13 AND STURGIS WATER SPECS. PIPE DEFLECTION IS PROHIBITED. PIPE RESTRAINT DEVICES AND LABOR SHALL E INCIDENTAL TO THE COST OF THE WATER MAIN INSTALLATION AND NO ADDITIONAL PAYMENT WILL BE MADE.
- WATER SERVICE DISCONNECTION/RECONNECTION EXISTING SERVICES SHALL BE DISCONNECTED AND RECONNECTED TO THE NEW MAIN AS SHOWN ON THE PLANS. A TAPPING SADDLE AND CORPORATION STOP SHALL BE INSTALLED FOR EACH SERVICE CONNECTION. A SERVICE LINE SHALL BE INSTALLED FROM THE CORPORATION STOP. WATER SERVICES SCHEDULED FOR DISCONNECTION FROM THE EXISTING MAIN AS SHOWN IN THE PLANS SHALL BE DISCONNECTED BY EXPOSING AND SHUTTING THE CORPORATION STOP AND CUTTING AND CAPPING OR PLUGGING THE LINE USING A MANUFACTURED CAP OR PLUG. EXISTING CURB STOP BOX TO BE REMOVED AS PART OF DISCONNECT. EXISTING DISCONNECTED SERVICE LINES SHALL BE ABANDONED IN PLACE.
- THRUST BLOCKS SHALL BE PROVIDED AT FIRE HYDRANTS AND OTHER SELECT FITTINGS AS SHOWN IN THE DETAILS. REFER TO THE THRUST BLOCK DETAIL FOR SIZING. THRUST BLOCKS SHALL BE CURED FOR AT LEAST 4 HOURS BEFORE BEING COVERED AND AT LEAST 48 HOURS PRIOR TO THE MAIN BEING ACTIVATED. THRUST BLOCKS ARE CONSIDERED INCIDENTAL TO WATER MAIN INSTALLATION AND NO ADDITIONAL PAYMENT WILL BE MADE
- ALL VALVE BOXES SHALL BE RATED "HEAVY DUTY".
- 13. THE CONTRACTOR SHALL BE RESPONSIBLE FOR NOTIFYING SOUTH DAKOTA ONE CALL 1-800-781-7474 TO HAVE UTILITIES FIELD LOCATED.

MATERIALS MANAGEMENT NOTES

- DUE TO LIMITED SITE STORAGE AREA, ALL UNSUITABLE EXCAVATED MATERIAL WILL BE DISPOSED OF OFF SITE AND IS THE RESPONSIBILITY OF THE CONTRACTOR. CONTRACTOR WILL NEED TO INFORM THE OWNER OF OFFSITE DISPOSAL OF EXCAVATED MATERIAL
- IN THE EVENT OF A SPILL OR IF CONTAMINATED MATERIAL IS ENCOUNTERED, INFORM THE OWNER AND ENGINEER, AND CONTACT THE SDANR TO DETERMINE APPROPRIATE ACTION.
- CONTRACTOR SHALL DISPOSE OF ALL MISCELLANEOUS DEBRIS EXCAVATED ON THE PROJECT.
- CONTRACTOR SHALL COMPLETE STREET CLEANING OF CONSTRUCTION DEBRIS TRACKED OFF CONSTRUCTION SITE DURING MOBILIZATION, CONSTRUCTION ACTIVITIES AND DEMOBILIZATION.

SUBSURFACE UTILITY INFORMATION

WHERE PUBLIC UTILITY FIXTURES ARE SHOWN AS EXISTING ON THE PLANS OR ENCOUNTERED WITHIN THE CONSTRUCTION AREA, IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO NOTIFY THE OWNERS OF THOSE UTILITIES PRIOR TO THE BEGINNING OF ANY CONSTRUCTION. THE CONTRACTOR SHALL AFFORD ACCESS TO THESE FACILITIES FOR NECESSARY MODIFICATION OF SERVICES, LINDERGROUND FACILITIES, STRUCTURES AND UTILITIES HAVE BEEN PLOTTED FROM AVAILABLE SURVEYS AND RECORDS, AND THEREFORE THEIR LOCATIONS MUST BE CONSIDERED APPROXIMATE ONLY. IT IS POSSIBLE THERE MAY BE OTHERS, THE EXISTENCE OF WHICH PRESENTLY NOT KNOWN OR SHOWN. IT IS THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THEIR EXISTENCE AND EXACT LOCATION AND TO AVOID DAMAGE THERETO. NO CLAIMS FOR ADDITIONAL COMPENSATION WILL BE ALLOWED TO THE CONTRACTOR FOR ANY INTERFERENCE OR DELAY CAUSE BY SUCH

GENERAL PROJECT NOTES

THE SUBSURFACE UTILITY INFORMATION SHOWN WITHIN THIS PLAN SET IS SHOWN TO UTILITY QUALITY LEVEL IN ACCORDANCE WITH THE LEGEND PROVIDED BELOW. THIS QUALITY LEVEL WAS DETERMINED ACCORDING TO THE GUIDELINES OF CI/ASCE38-02, ENTITLES STANDARD GUIDELINES FOR THE COLLECTION AND DEPICTION OF EXISTING SUBSURFACE UTILITY

UTILITY QUALITY LEVELS

- LEVEL D -INFORMATION COMES SOLELY FROM EXISTING UTILITY RECORDS
- LEVEL C -SURVEYING ABOVE GROUND UTILITY FACILITIES, SUCH AS MANHOLES, VALVE BOXES, ETC; AND CORRELATING THIS INFORMATION WITH EXISTING UTILITY RECORDS.
- THE USE OF SURFACE GEOPHYSICAL TECHNIQUES TO DETERMINE THE EXISTENCE AND HORIZONTAL POSITION LEVEL B -OF UNDERGROUND UTILITIES.
- THE USE OF NONDESTRUCTIVE DIGGING FOUIPMENT AT HORIZONTAL AND VERTICAL POSITION OF LEVEL A -
- UNDERGROUND UTILITIES, AS WELL AS THE TYPE, SIZE, CONDITION, MATERIAL AND OTHER CHARACTERISTICS

THE UNDERGROUND UTILITIES IN THIS DRAWING SET FOR THIS PROJECT ARE AS FOLLOWS: LEVEL D/C

GRADE STAKES, BENCHMARKS AND MONUMENTS

- THE CONTRACTOR IS RESPONSIBLE FOR SURVEYING AND STAKING DURING THE PROJECT.
- ALL STAKES, STONES, AND MONUMENTS NOW IN PLACE AND MARKING LINES AND CORNERS OF BOUNDARIES WHICH ARE LIKELY TO BE AFFECTED BY THE WORK HEREIN PROVIDED FOR SHALL BE CAREFULLY PRESERVED BY THE CONTRACTOR. IN NO CASE SHALL ANY EXCAVATION BE MADE WITHIN FIVE FEET (5') OF ANY SUCH STAKE, STONE OR MONUMENT UNTIL THEY HAVE BEEN PROPERLY RESET, WITNESSED, OR OTHERWISE CARED FOR BY A SD LICENSED SURVEYOR AND PERMISSION IS GIVEN TO

SUBMITTALS

- CONTRACTOR IS REQUIRED TO SUBMIT THE FOLLOWING ITEMS TO THE CITY FOR APPROVAL PRIOR TO BEGINNING CONSTRUCTION. ALL MATERIAL MUST BE NEW.
- CONSTRUCTION SCHEDULE
- TRAFFIC CONTROL PLAN
- ASPHALT AND CONCRETE MIXES 1.3.
- AGGREGATE BASE GRADATION
- SHOP DRAWINGS OR PRODUCT LISTS WATER SHOP DRAWINGS.
- 1.6.
- SANITARY SEWER SHOP DRAWINGS (MANHOLES, ETC.).
- CMP CULVERTS AND ENDS

CONSTRUCTION SCHEDULE

- THE CONTRACTOR SHALL PREPARE A CONSTRUCTION SCHEDULE FOR APPROVAL TO THE ENGINEER THAT WILL ENSURE THE COMPLETION OF THE PROJECT WITHIN THE TIME FRAME SPECIFIED. THIS SCHEDULE MUST BE PROVIDED TO THE ENGINEER FOR REVIEW A MINIMUM OF 3 DAYS PRIOR TO THE PRECONSTRUCTION MEETING. THE NOTICE TO PROCEED WILL NOT BE ISSUED UNTIL THE SCHEDULE HAS BEEN APPROVED BY THE CITY. THE CONSTRUCTION SCHEDULE SHALL BE IN BAR OR NETWORK DIAGRAM FORM AND SHOW THE START AND COMPLETION DATES FOR SIGNIFICANT ITEMS OF WORK IN THEIR RESPECTIVE PHASES, SIGNIFICANT ITEMS OF WORK INCLUDES BUT IS NOT LIMITED TO: EROSION CONTROL REMOVALS. GRADING, SANITARY SEWER, BASE COURSE, PAVING LAYER, AND RESTORATION, WHEN APPLICABLE THE SCHEDULE SHALL INCLUDE SUBMISSION DATES FOR SHOP DRAWINGS, MANUFACTURING AND INSTALLATION OF MATERIALS, SUPPLIES, EQUIPMENT, AND TESTING FOR VARIOUS PARTS OF THE WORK.
- THE CONSTRUCTION SCHEDULE SHALL BE UPDATED ON A BI-WEEKLY BASIS. IF IT APPEARS THE RATE OF PROGRESS IS SUCH THAT THE CONTRACT WILL NOT BE COMPLETED WITHIN THE TIME FRAME ALLOWED THE CONTRACTOR WILL BE REQUIRED TO PROVIDE WRITTEN DOCUMENTATION AS TO WHAT MEASURES THEY WILL TAKE TO COMPLETE THE PROJECT WITHIN THE SPECIFIED TIME FRAME OR TO PROSECUTE WORK IN A SATISFACTORY MANNER
- THE CONTRACTOR WILL APPOINT SOMEONE TO INTERFACE WITH THE PROPERTY OWNERS AFFECTED BY CONSTRUCTION THE CONTRACTOR WILL PROVIDE SCHEDULES OF WHEN ANY WORK WILL BE DONE THAT AFFECTS TRAFFIC ON DOLAN CREEK ROAD. THE CONTRACTOR WILL CONTACT EACH LANDOWNER EACH TIME THE LANDOWNERS WILL BE IMPACTED. THE CITY ENGINEER RESERVES THE RIGHT TO DIRECT THE CONTRACTOR TO CHANGE THE MODE OF COMMUNICATION TO MEET THE NEEDS OF THE LANDOWNERS.
- CONTRACTOR MAY ONLY WORK ON WATERLINE PORTION DURING NORMAL BUSINESS HOURS 7 AM-7 PM M-S.
- NO PROPERTY SHALL BE WITHOUT WATER OR SANITARY SEWER SERVICE FOR MORE THAN EIGHT HOURS. EACH PROPERTY SHALL RECEIVE A TWO DAY NOTICE OF ANY SERVICE DISRUPTION.
- TRASH PICKUP THE CONTRACTOR SHALL PROVIDE NOTIFICATION OF WORK TO ALL AFFECTED PROPERTY OWNERS AND COORDINATE WITH SOLID WASTE COLLECTION CONTRACTORS.
- MAIL DELIVERY CONTRACTOR SHALL COORDINATE WITH THE POSTAL SERVICE FOR MAIL DELIVERY TO ALL PROPERTIES WATERCTED BY THE PROJECT. EXISTING CURB SIDE MAILBOXES SHALL BE RELOCATED AS NEEDED AND AS APPROVED BY OWNER AND POSTAL SERVICE. NO SEPARATE PAYMENT SHALL BE MADE FOR THIS WORK.

INCIDENTAL WORK

THE FOLLOWING ITEMS SHALL BE INCIDENTAL TO OTHER ITEMS OF WORK. INCIDENTAL WORK SHALL INCLUDE ALL MISCELLANEOUS ITEMS NOT INCLUDED IN THE REGULAR ITEMS COVERED BY UNIT PRICES IN THE PROPOSAL BUT WHICH MUST BE PERFORMED IN ORDER TO PROPERLY COMPLETE THE WORK. THUS, THIS IS NOT A COMPREHENSIVE LIST



NO DATE BY REVISION DESCRIPTION CLIENT PROJECT NO: PINE GLENN FOTH PROJECT NO: 21S100.00 DESIGNED BY: KRM CHECKED BY: TFS DRAWN BY: MLH 8:25:22 AM CAD DATE: 5/2/2022 LETTING DATE:



PINE GLENN STREET AND UTILITY IMPROVEMENTS

STURGIS, SOUTH DAKOTA

GENERAL GENERAL PROJECT NOTES

G0.02

STORMWATER POLLUTION PREVENTION PLAN (SWPPP)

Also known as an Erosion and Sediment Control Plan (ESCP)

NARRATIVE

CITY OF STURGIS 1040 HARLEY-DAVIDSON WAY STURGIS, SD 57785

CITY MANAGER: DANIEL AINSLIE EMAIL ADDRESS: DAINSLIE@STURGISGOV.COM PHONE NUMBER: 605 347-4422

DESIGN ENGINEER

501 NINTH STREET - SUITE 200

RAPID CITY, SD 57701 REGISTERED ENGINEER: TED F. SCHULTZ EMAIL ADDRESS: TED.SCHULTZ@FOTH.COM

PHONE NUMBER: 605 381-0433

THIS SWPPP APPEARS TO FULFILL THE TECHNICAL CRITERIA FOR EROSION CONTROL AND THE REQUIREMENTS OF THE CITY OF STURGIS. I UNDERSTAND THAT ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES MAY BE NEEDED IF UNFORESEEN EROSION PROBLEMS OCCUR OR IF THE SUBMITTED PLAN DOES NOT FUNCTION AS INTENDED. THE REQUIREMENTS OF THIS PLAN SHALL RUN WITH THE LAND AND BE THE OBLIGATION OF THE PRIMARY RESPONSIBLE PARTY UNTIL SUCH TIME AS THE PLAN IS PROPERLY COMPLETED, MODIFIED OR VOIDED.

DNED:	
	NAME/TITLE

THE ENGINEER WILL BE RESPONSIBLE TO MAINTAIN AN ORIGINAL COPY OF THE SWPPP. ANY MODIFICATIONS TO THE SWPPP MUST BE DOCUMENTED AND MADE PART OF THE SWPPP.

PRIME CONTRACTOR

- THE "DEPARTMENT OF AGRICULTURE AND NATURAL RESOURCES CONTRACTOR CERTIFICATION FORM" (SD FORM 2110LD) IS TO BE EXECUTED BY THE PRIME CONTRACTOR OR HIS REPRESENTATIVE AFTER THE AWARD OF THE CONTRACT. WORK MAY NOT BEGIN ON THE PROJECT UNTIL THIS SECTION IS SIGNED.
- THE FORM CERTIFIES UNDER PENALTY OF LAW THAT THE CONTRACTOR UNDERSTANDS AND WILL COMPLY WITH THE TERMS AND CONDITIONS OF THE SURFACE WATER DISCHARGE GENERAL PERMIT FOR STORM WATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITIES FOR THE PROJECT.

A NOTICE OF INTENT (NOI) FOR COVERAGE UNDER THE GENERAL PERMIT FOR STORM WATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITIES WILL BE FOLLOWED. A COPY OF THE PERMIT MUST BE KEPT ON SITE AT THE CONTRACTOR STAGING AREA. A GENERIC COPY MAY BE DOWNLOADED FROM

https://danr.sd.gov/OfficeOfWater/SurfaceWaterQualtiy/stormwater/StormWaterConstruction.aspx

MODIFICATIONS TO THE SWPPP

THE ENGINEER MAY ORDER CHANGES TO THE SWPPP AND/OR THE CONTRACTOR IS RESPONSIBLE TO REQUEST CHANGES TO THE SWPPP IF UNFORESEEN CHANGES OCCUR. OR THE SWPPP DOES NOT PERFORM AS INTENDED. OR TO IMPROVE THE EFFECTIVENESS OF THE SWPPP, OR TO COMPLY WITH THE SD DNR PERMIT. THE ENGINEER WILL EVALUATE AND DETERMINE IF ANY CONTRACTOR REQUESTED CHANGES TO THE SWPPP SHOULD BE MADE. THE CONTRACTOR IS RESPONSIBLE TO IMPLEMENT THESE CHANGES AS SOON AS PRACTICAL. ALL APPROVED CHANGES TO THE SWPPP MUST BE DOCUMENTED BY THE ENGINEER.

KEEPING THE SWPPP CURRENT

INSPECTIONS

- THE CONTRACTOR WILL BE REQUIRED TO PERFORM INSPECTIONS ON THE PROJECT AT THE FOLLOWING MINIMUM FREQUENCY UNTIL THE SITE HAS REACHED FINAL STABILIZATION AND A NOTICE OF TERMINATION IS SUBMITTED TO THE SDDNR
- PRIOR TO THE REMOVAL OF ANY SURFACING OR TOPSOIL.
- ONCE EVERY SEVEN CALENDAR DAYS (MINIMUM). WHEN RUNOFF IS UNLIKELY DUE TO WINTER CONDITIONS THE INSPECTIONS MAY BE REDUCED TO ONCE A MONTH.
- WITHIN 24 HOURS AFTER EVERY RAINFALL OF 1/2 INCH OR GREATER.
- AFTER A SNOW MELT THAT CAUSES FROSION.
- WITHIN 24 HOURS OF A COMPLAINT BEING MADE TO THE CONTRACTOR OR ENGINEER.
- THE ENGINEER RESERVES TO RIGHT TO PERFORM INSPECTIONS MORE FREQUENTLY THAN IDENTIFIED AND ADDITIONAL INSPECTIONS WILL BE MADE IF OBVIOUS ITEMS OF NON-COMPLIANCE EXIST. IF THE CONTRACTOR FAILS TO ATTEND ANY INSPECTION IT DOES NOT RELIEVE THEM OF THEIR RESPONSIBILITY TO COMPLY WITH ANY CORRECTIVE OR MAINTENANCE
- ITEMS NOTED AS BEING NON-COMPLIANT OR NEEDING MAINTENANCE AS A RESULT OF THE INSPECTIONS MUST BE CORRECTED AS SOON AS PRACTICAL. THE SITE SHALL CONTINUE TO BE CONSIDERED IN NON-COMPLIANCE UNTIL THE ISSUE HAS BEEN CORRECTED TO THE SATISFACTION OF THE ENGINEER

NOTICE OF TERMINATION

CLIENT PROJECT NO: PINE GLENN

DESIGNED BY:

I FITTING DATE:

- THE CONTRACTOR IS RESPONSIBLE FOR COMPLYING WITH THE SWPPP UNTIL A NOTICE OF TERMINATION (NOT) OF COVERAGE UNDER THE GENERAL PERMIT HAS BEEN ISSUED. THE N.O.T. WILL BE PREPARED BY THE CONTRACTOR FOR SUBMITTAL TO THE CITY AND THEN THE SDDENR WHEN ALL STORM WATER DISCHARGES COVERED BY THE PERMIT ARE FLIMINATED AND FINAL STABILIZATION HAS BEEN ACHIEVED ON ALL PORTIONS OF THE SITE FOR WHICH THE PERMITTEE IS RESPONSIBLE. FINAL STABILIZATION MEANS EITHER OR A COMBINATION OF:
- ALL SOIL DISTURBING ACTIVITIES AT THE SITE HAVE BEEN COMPLETED AND A UNIFORM PERENNIAL VEGETATIVE COVER WITH A DENSITY OF 70% OF THE NATIVE COVER FOR UNPAVED AREAS AND AREAS NOT COVERED BY PERMANENT STRUCTURES HAS BEEN ESTABLISHED, OR EQUIVALENT PERMANENT STABILIZATION MEASURES (SUCH AS THE USE OF RIPRAP, GABIONS, OR GEOTEXTILES) HAVE BEEN EMPLOYED: OR
- FOR CONSTRUCTION PROJECTS ON LAND USED FOR AGRICULTURAL PURPOSES, FINAL STABILIZATION MAY BE 1.2. ACCOMPLISHED BY RETURNING THE DISTURBED LAND TO ITS PRE-CONSTRUCTION AGRICULTURAL USE. AREAS

MLH

8:25:28 AM

O DATE

FOTH PROJECT NO: 21S100.00

REVISION DESCRIPTION

STORMWATER POLLUTION PREVENTION PLAN (SWPPP)

Also known as an Erosion and Sediment Control Plan (ESCP)

DISTURBED THAT WERE NOT PREVIOUSLY USED FOR AGRICULTURAL ACTIVITIES, SUCH AS BUFFER STRIPS IMMEDIATELY ADJACENT TO "WATERS OF THE STATE," AND AREAS WHICH ARE NOT BEING RETURNED TO THEIR PRE-CONSTRUCTION AGRICULTURAL USE MUST MEET THE FINAL STABILIZATION CRITERIA IN (1) ABOVE.

PROJECT DESCRIPTION

THIS PROJECT CONSISTS OF A WATER LINE, SANITARY SEWER, AGGREGATE BASE COURSE, AND ASPHALT PAVEMENT PATCHING. THE CONTRACTOR IS NOT ALLOWED TO WORK IN THE CHANNEL, AND MUST PROTECT MATERIAL FROM GOING IN

EXISTING SITE CONDITIONS

THE EXISTING SITE IS GRASS, AND SMALL COBBLES. THE EXISTING SOIL IS SILTY CLAY WITH SMALL COBBLES. THE EXISTING PINE GLENN DRIVE IS GRAVEL AND DIRT SOUTH OF DOLAN CREEK ROAD. THE EXISTING PINE GLENN DRIVE IS ASPHALT

ADJACENT AREAS

1. THE SURROUNDING AREAS CONSIST OF PRIVATE PROPERTY MOSTLY BEING LOW DENSITY.

AREA AND VOLUME DISTURBED

THE TOTAL SURFACE AREA TO BE DISTURBED DURING THIS PHASE IS APPROXIMATELY 1.1 ACRES. IT IS ESTIMATED THAT THE FINAL GRADE WILL BE SIMILAR TO EXISTING AFTER INSTALLATION OF THE WATER AND SANITARY SEWER LINES.

EROSION/SEDIMENT CONTROL SEQUENCE AND TIME SCHEDULE

PLACE SEED MIX NO MORE THAN 14 DAYS AFTER FINAL GRADING IS COMPLETE.

PERMANENT STABILIZATION MEASURES

SEED WILL BE USED FOR PERMANENT STABILIZATION OF ALL DISTURBED AREAS NOT PAVED THROUGHOUT THE PROJECT

GOOD HOUSEKEEPING

- NONSTRUCTURAL BMPS SUCH AS GOOD HOUSEKEEPING MEASURES CAN, TO SOME DEGREE, PREVENT THE DEPOSITION OF POLLUTANTS ON THE URBAN LANDSCAPE OR REMOVE POLLUTANTS AT THEIR SOURCE. THE SOURCE OF POLLUTANTS FOR ASSIMILATION INTO STORM WATER IS THE LAND SURFACE ITSELF, ESPECIALLY THE IMPERVIOUS SURFACES IN THE URBAN AREA. THUS, IT IS EXPECTED THAT WHEN NONSTRUCTURAL MEASURES ARE EFFECTIVELY IMPLEMENTED, THEY WILL REDUCE THE AMOUNT OF POLLUTANTS BEING DEPOSITED ON LAND SURFACES FOR EVENTUAL CONTACT WITH STORM WATER AND TRANSPORTED TO THE RECEIVING WATER SYSTEM. THEREFORE, THE CONTRACTOR SHOULD EVALUATE AND DETERMINE WHICH APPROPRIATE GOOD HOUSEKEEPING MEASURES LISTED BELOW COULD BE USED.
- OPERATION AND MAINTENANCE: TO ASSURE THAT EQUIPMENT AND WORK RELATED PROCESSES ARE WORKING WELL, THE FOLLOWING PRACTICES CAN BE IMPLEMENTED:
- MAINTAIN DRY AND CLEAN FLOORS AND GROUND SURFACES BY USING BROOMS, SHOVELS, VACUUM CLEANERS, OR CLEANING MACHINES RATHER THAN WET CLEANUP METHODS.
- REGULARLY PICK UP AND DISPOSE OF GARBAGE AND WASTE MATERIAL
- MAKE SURE ALL EQUIPMENT AND RELATED PROCESSES ARE WORKING PROPERLY AND PREVENTATIVE MAINTENANCE IS KEPT UP WITH ON BOTH.
- 2.4 ROUTINELY INSPECT EQUIPMENT AND PROCESSES FOR LEAKS OR CONDITIONS THAT COULD LEAD TO DISCHARGES OF CHEMICALS OR CONTACT OF STORM WATER WITH RAW MATERIALS, INTERMEDIATE MATERIALS, WASTE MATERIALS, OR PRODUCTS USED ON SITE.
- ASSURE ALL SPILL CLEANUP PROCEDURES ARE UNDERSTOOD BY EMPLOYEES. TRAINING OF EMPLOYEES ON PROPER CLEANUP PROCEDURES SHALL BE IMPLEMENTED
- DESIGNATE SEPARATE AREAS OF THE SITE FOR AUTO PARKING, VEHICLE REFUELING, AND ROUTINE MAINTENANCE.
- CLEAN UP LEAKS, DRIPS, AND OTHER SPILLS IMMEDIATELY.
- 2.8. COVER AND MAINTAIN DUMPSTERS AND WASTE RECEPTACLES
- MATERIAL STORAGE PRACTICES: IMPROPERLY STORING MATERIAL ON SITE CAN LEAD TO THE RELEASE OF MATERIALS AND CHEMICALS THAT CAN CAUSE STORM WATER RUNOFF POLLUTION. PROPER STORAGE TECHNIQUES INCLUDE THE FOLLOWING:
- PROVIDE ADEQUATE AISLE SPACE TO FACILITATE MATERIAL TRANSFER AND EASE OF ACCESS FOR INSPECTION STORE CONTAINERS, DRUMS, AND BAGS AWAY FROM DIRECT TRAFFIC ROUTES TO PREVENT ACCIDENTAL SPILLS. 3 STACK CONTAINERS ACCORDING TO MANUFACTURER'S INSTRUCTIONS TO AVOID DAMAGING THE CONTAINERS FROM IMPROPER WEIGHT DISTRIBUTION 4. STORE CONTAINERS ON PALLETS OR SIMILAR DEVICES TO PREVENT CORROSION OF CONTAINERS THAT RESULTS FROM CONTAINERS COMING IN CONTACT WITH MOISTURE ON THE GROUND. 5. STORE TOXIC OR HAZARDOUS LIQUIDS WITHIN CURBED AREAS OR SECONDARY CONTAINERS.
- ASSIGN RESPONSIBILITY OF HAZARDOUS MATERIAL INVENTORY TO A LIMITED NUMBER OF PEOPLE WHO ARE TRAINED TO HANDLE SUCH MATERIALS.
- MATERIAL INVENTORY PRACTICES, AN UP-TO-DATE INVENTORY KEPT ON ALL MATERIALS (BOTH HAZARDOUS AND NONHAZARDOUS) PRESENT ON SITE WILL HELP TRACK HOW MATERIALS ARE STORED AND HANDLED ONSITE, AND IDENTIFY WHICH MATERIALS AND ACTIVITIES POSE THE MOST RISK TO THE ENVIRONMENT. THE FOLLOWING DESCRIPTION PROVIDES THE BASIC STEPS IN COMPLETING A MATERIAL INVENTORY:
- IDENTIFY ALL CHEMICAL SUBSTANCES PRESENT AT WORK SITE, PERFORM A WALK-THROUGH OF THE SITE, REVIEW PURCHASE ORDERS, LIST ALL CHEMICAL SUBSTANCES USED, AND OBTAIN MATERIAL SAFETY DATA SHEETS (MSDS) FOR ALL CHEMICALS. NAME AND TYPE OF SUBSTANCE, STOCK NUMBER
- LABEL ALL CONTAINERS, LABELS SHALL PROVIDE EXPIRATION DATE, HEALTH HAZARDS, HANDLING SUGGESTIONS, AND FIRST AID INFORMATION, THIS INFORMATION CAN ALSO BE FOUND ON AN MSDS. INVENTORY WHICH CHEMICALS REQUIRE SPECIAL
- CLEARLY MARK ON THE HAZARDOUS MATERIALS HANDLING, STORAGE, USE, AND DISPOSAL CONSIDERATIONS DECISIONS ON THE AMOUNTS OF HAZARDOUS MATERIALS THAT ARE STORED ON SITE SHALL INCLUDE AN EVALUATION OF ANY EMERGENCY CONTROL SYSTEMS THAT ARE IN PLACE. ALL STORAGE AREAS SHALL BE DESIGNED TO CONTAIN
- TRAINING AND PARTICIPATION, FREQUENT AND PROPER TRAINING IN GOOD HOUSEKEEPING TECHNIQUES REDUCES THE

STORMWATER POLLUTION PREVENTION PLAN (SWPPP)

POSSIBILITY OF CHEMICALS OR EQUIPMENT THAT WILL BE MISHANDLED. REDUCING WASTE GENERATION IS ANOTHER IMPORTANT POLLUTION PREVENTION TECHNIQUE. THE FOLLOWING ARE WAYS TO GET PEOPLE INVOLVED IN GOOD

- PROVIDE INFORMATION SESSIONS ON GOOD HOUSEKEEPING PRACTICES IN TRAINING PROGRAMS.
- DISCUSS GOOD HOUSEKEEPING AT MEETINGS.
- PUBLICIZE POLLUTION PREVENTION CONCEPTS THROUGH POSTERS OR SIGNS

METHODS OF ENSURING SURFACE WATER QUALITY

- THE CONTRACTOR SHALL BE RESPONSIBLE TO ENSURE NO SEDIMENT LADEN WATERS LEAVE THE PROJECT WITHOUT EXPOSURE TO AN EROSION OR SEDIMENT CONTROL DEVICE.
- 2. THE ONLY NON STORM WATER DISCHARGE ALLOWED BY THE GENERAL PERMIT FOR STORM WATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITIES IS UNCONTAMINATED GROUND WATER OR WATERS, USED AS A BEST MANAGEMENT PRACTICE. TO WASH VEHICLES AND CONTROL DUST. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO OBTAIN A GENERAL PERMIT TO DISCHARGE UNDER THE SOUTH DAKOTA SURFACE WATER DISCHARGE SYSTEM FOR TEMPORARY DISCHARGE ACTIVITIES IN SOLITH DAKOTA (DEWATERING PERMIT) FOR ALL OTHER NON STORM WATER DISCHARGES. ALL MONITORING, TESTING, AND OTHER REQUIREMENTS OF THE DEWATERING PERMIT ARE THE RESPONSIBILITY OF THE CONTRACTOR
- PUMPING (MECHANICALLY DISCHARGING) SEDIMENT LADEN WATER INCLUDING PONDED STORM WATER OR CONTAMINATED TRENCH DEWATERING INTO THE STORM SEWER OR OFF THE PROJECT SITE IS NOT COVERED UNDER THE GENERAL PERMIT. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO OBTAIN AND COMPLY WITH A DEWATERING PERMIT FOR THESE ACTIVITIES. THE ENGINEER MAY NOTIFY THE SDDENR IF THE CONTRACTOR IS OBSERVED PUMPING SEDIMENT LADEN WATER INTO THE STORM SEWER OR OFF SITE. PUMPING SEDIMENT LADEN WATER THROUGH INLET PROTECTION IS NOT ALLOWED AS A BMP.
- IN LIEU OF PUMPING SEDIMENT LADEN WATER THE FOLLOWING ARE SOME METHODS THE CONTRACTOR MAY USE TO CONTROL SEDIMENT LADEN WATER
- 4.1. THE BEST METHOD IS FOR THE CONTRACTOR TO MAINTAIN POSITIVE DRAINAGE DURING ALL PHASES OF THE PROJECT TO PREVENT WATER FROM PONDING ON THE PROJECT.
- 4.2. TREAT THE SEDIMENT LADEN WATER ONSITE THROUGH THE USE OF FILTER BAGS, DEFLOCCULATING CHEMICALS, SEDIMENT BASINS OR A PORTABLE CONTAINMENT SYSTEM.
- 4.3. PUMP OR DISCHARGE THE WATER TO OTHER PORTIONS OF THE SITE. THIS IS ALLOWED IF THE WATERS DO NOT LEAVE THE PROJECT LIMITS.
- NO PAYMENT WILL BE MADE TO THE CONTRACTOR TO COMPLY WITH A DEWATERING PERMIT UNLESS OTHERWISE SPECIFIED AND IT WILL BE CONSIDERED INCIDENTAL TO THE VARIOUS BID ITEMS.

SEDIMENT CONTROL MEASURES

INSTALLATION OF SEDIMENT CONTROL MEASURES

THE CONTRACTOR SHALL NOT BEGIN THE REMOVAL OF SURFACING OR TOPSOIL WITHIN THE APPLICABLE WORK AREA UNTIL ALL APPLICABLE SEDIMENT CONTROL MEASURES ARE PLACED. SEDIMENT CONTROL MEASURES SHALL BE INSTALLED AS NECESSARY AS CONSTRUCTION PROGRESSES AND THESE SEDIMENT CONTROL DEVICES SHALL BE INSTALLED WITHIN 24 HOURS AT LOCATIONS IDENTIFIED ON THE SWPPE

PERMANENT EROSION CONTROL MEASURES

- THE FOLLOWING INFORMATION IS TO PROVIDE AN INFORMATIONAL GUIDELINE TO THE CONTRACTOR REGARDING TOPSOIL PLACEMENT AND THE SWPPE
- GENERALLY, TOPSOIL WILL BE PLACED OVER ALL DISTURBED AREAS TO A DEPTH OF 6 INCHES. THE PLACEMENT OF THE TOPSOIL SHALL BE AS SOON AS POSSIBLE UPON COMPLETION OF THE GRADING OPERATIONS. TOPSOIL WILL BE PLACED OVER ALL DISTURBED AREAS TO A DEPTH OF 6 INCHES LINEESS OTHERWISE SPECIFIED BY THE ENGINEER. THE PLACEMENT OF THE TOPSOIL SHALL BE COMPLETED WITHIN 5 DAYS OF FINAL GRADING. SOIL STABILIZATION SHALL BE IN ACCORDANCE
- CONTRACTOR FURNISHED TOPSOIL: TOPSOIL PLACED SHALL BE SCREENED AND PULVERIZED AND MEET THE REQUIREMENTS OF THE FOLLOWING TABLE:

TOPSOIL REQUIREMENTS	MINIMUM	MAXIMUM
MATERIAL PASSING #10 SIEVE	95%	*
CLAY	5%	50%
SILT	10%	70%
SAND AND GRAVEL	10%	60%
ORGANIC MATTER (AS DETERMINED BY WEIGHT)	4%	15%
pH (ASTM D 5268)	6.0	8.0

THE TOPSOIL PROVIDED SHALL BE SMOOTH, UNIFORM, AND FREE OF STONES 1 INCH OR LARGER IN ANY DIMENSION, ROOTS AND OTHER EXTRANEOUS OR UNDESIRABLE MATERIA HARMFUL TO PLANT GROWTH. THE CONTRACTOR SHALL SUBMIT TO THE ENGINEER THE PROSPECTIVE SOURCE FOR THE TOPSOIL AT LEAST 1 MONTH PRIOR TO TIME OF PLACEMENT TO ALLOW ADEQUATE TIME FOR INSPECTING, TESTING AND APPROVING THE SOURCE. A COMPANION TOPSOIL TEST MAY BE PERFORMED ON SITE AFTER PLACEMENT. TEXTURE SHALL BE DETERMINED BY THE METHOD DESCRIBED IN AASHTO T 88.



CIVIL STANDARDS STORMWATER POLLUTION PREVENTION PLAN

PINE GLENN STREET AND UTILITY IMPROVEMENTS

KRM CHECKED BY: TFS DRAWN BY:

CAD DATE: 5/2/2022

STORMWATER POLLUTION PREVENTION PLAN (SWPPP)

Also known as an Erosion and Sediment Control Plan (ESCP)

PERMANENT EROSION CONTROL MEASURES - (CONT)

SALVAGED TOPSOIL

IF THE CONTRACTOR CHOOSES TO USE CONTRACTOR FURNISHED TOPSOIL INSTEAD OF SALVAGED TOPSOIL, NO ADDITIONAL COMPENSATION WILL BE MADE FOR THEIR EFFORTS.

SEEDBED PREPARATION

THE INITIAL PREPARATION OF THE NEWLY GRADED AREA FOR SEEDING SHALL CONSIST OF REMOVING EXISTING GRASS VEGETATION AND TURF. DO NOT MIX INTO TOPSOIL. LOOSEN SOIL TO A DEPTH OF AT LEAST 6 INCHES. REMOVE STONES LARGER THAN 1" IN ANY DIMENSION, STICKS, ROOTS, TRASH AND OTHER EXTRANEOUS MATTER. GRADE THE PLANTING AREAS TO A SMOOTH, UNIFORM SURFACE THAT IS LOOSE AND UNIFORMLY FINE TEXTURED. GRADE TO WITHIN +/- 0.5" OF THE FINISH FLEVATION, ROLL AND RAKE, REMOVE RIDGES, PULVERIZE SOIL CLODS TO LESS THAN 1" AND FILL DEPRESSIONS. TO MEET FINISH GRADES. THE CONTRACTOR WILL NEED PRIOR AUTHORIZATION FROM THE ENGINEER TO COMMENCE SEEDING. SEEDBED PREPARATION SHALL BE INCIDENTAL TO THE APPROPRIATE "SEED MIXTURE" PAY ITEM.

SEED TESTING

SEED SHALL BE TESTED WITHIN 9 MONTHS PRIOR TO PLANTING, EXCLUSIVE OF THE CALENDAR MONTH IN WHICH THE TEST WAS COMPLETED. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH SD STANDARD SPECIFICATION FOR ROADS AND BRIDGES SECTION 730.2C. THE CERTIFIED TEST REPORT SHALL BE FURNISHED TO THE ENGINEER PRIOR TO THE START OF THE SEEDING OPERATIONS.

EACH BAG OF SEED DELIVERED TO THE PROJECT SHALL BEAR A TAG WHICH CONFORMS TO THE SD STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES SECTION 730.2D. THERE WILL BE NO PAYMENT FOR SEED USED WITHOUT THE

SEEDING

- CONSTRUCTION REQUIREMENTS: SEEDING AND FERTILIZING SHALL COMPLY WITH SECTIONS 730 AND 731 OF THE SDDOT STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES. IF THE SEASONAL LIMITATIONS FOR SEEDING AS SPECIFIED IN SECTION 730 INTERFERE WITH THE TIMEFRAME LISTED WITHIN THE SOIL SURFACE STABILIZATION PRACTICES SECTION, THEN AN ALTERNATE TEMPORARY SOIL STABILIZATION PRACTICE MUST BE USED. PAYMENT WILL BE MADE TO THE CONTRACTOR FOR THESE ALTERNATE PRACTICES IF CAUSED BY THE CONDITIONS AND SEQUENCING OF THE PLANS AND/OR SPECIFICATIONS AND NOT THE RESULT OF THE CONTRACTOR'S NEGLIGENCE.
- ANY AREAS DISTURBED BEYOND THE CONSTRUCTION LIMITS DUE TO CONTRACTOR'S CARELESSNESS SHALL BE RESTORED AT THE CONTRACTOR'S EXPENSE.

SEED MIX SECTION 730

- SEED SHALL BE A LAWN MIX TO MATCH EXISTING
- SEED SHALL BE PLACED APRIL 1 THROUGH JUNE 1 OR AUGUST 15 THROUGH SEPTEMBER 15.
- MAINTENANCE: BARE SPOTS OR LOCATIONS OF EROSION SHALL BE RE-SEEDED AND MAINTAINED BY THE CONTRACTOR FOR AN ADDITIONAL 4 WEEKS AND THE AREA HAS MET THE VEGETATIVE COVER WITH A DENSITY OF 70% OF THE NATIVE COVER FOR UNPAVED AREAS, THIS ADDITIONAL MATERIAL AND LABOR SHALL BE AT NO ADDITIONAL COST TO THE OWNER.
- SEED WILL BE MEASURED AND PAID FOR IN ACCORDANCE WITH THE SD STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES SECTION 730 4 AND 730 5
- SEED SHALL BE DELIVERED TO THE PROJECT IN BAGS WITH SEED TAGS ATTACHED. THE TAGS WILL BE COLLECTED FROM THE
- MAINTENANCE: MAINTAIN AND ESTABLISH TURF FOR 45 DAYS BY WATERING, FERTILIZING, WEEDING, MOWING, TRIMMING, REPLANTING AND PERFORMING OTHER OPERATIONS AS REQUIRED TO ESTABLISH HEALTHY, VIABLE TURF. ROLL, REGRADE AND REPLANT BARE OR ERODED AREAS AND REMULCH TO PRODUCE A UNIFORMLY SMOOTH TURF. PROVIDE MATERIALS AND INSTALLATION THE SAME AS THOSE USED IN THE ORIGINAL INSTALLATION, FILL IN AS NECESSARY SOIL SUBSIDENCE THAT MAY OCCUR BECAUSE OF SETTLING OR OTHER PROCESSES. REPLACE MATERIALS AND TURF DAMAGED OR LOST IN AREAS OF
- BARE SPOTS OR LOCATIONS OF EROSION SHALL BE RE-SEEDED AND MAINTAINED BY THE CONTRACTOR FOR AN ADDITIONAL 45 DAYS AND UNTIL THE AREA HAS MET THE VEGETATIVE COVER REQUIREMENT OF 70% OF THE NATIVE COVER. THIS ADDITIONAL MATERIAL AND LABOR SHALL BE AT NO ADDITIONAL COST TO THE OWNER.
- SEED WILL BE MEASURED AND PAID FOR IN ACCORDANCE WITH THE SD STANDARD SPECIFICATIONS FOR ROADS AND BRIDGES SECTION 730.4 AND 730.5.

- THE CONTRACTOR SHALL APPLY AN ALL-NATURAL SLOW RELEASE FERTILIZER PRIOR TO SEEDING OR PLACING SOD. THE ALL-NATURAL FERTILIZER SHALL HAVE A MINIMUM GUARANTEED ANALYSIS OF 4-6-4 AND BE USDA CERTIFIED BIOBASED. IT SHOULD PROVIDE A MINIMUM OF 4% (N) NITROGEN WITH A MINIMUM WATER INSOLUBLE NITROGEN (WIN) FRACTION OF 3.2%, A MINIMUM OF 6% (P2O5) AVAILABLE PHOSPHATE, A MINIMUM OF 4% (K2O) SOLUBLE POTASH, AND A MAXIMUM CARBON TO NITROGEN RATIO (C:N RATIO) OF 5:1. THE ALL-NATURAL FERTILIZER SHALL BE FREE OF WEED-SEED AND PATHOGENS ACCOMPLISHED THROUGH THERMOPHILIC COMPOSTING, AND NOT MECHANICAL OR CHEMICAL STERILIZATION, TO ASSURE PRESENCE OF RENEFICIAL SOIL MICROBIOLOGY, THE FERTILIZER SHALL HAVE A NEAR NEUTRAL PH. A LOW SALT INDEX. A LOW BIOLOGICAL OXYGEN DEMAND, CONTAIN ORGANIC HUMIC AND FULVIC ACIDS, AND HAVE HIGH AEROBIC ORGANISM COUNTS. THE FERTILIZER SHALL ALSO BE STABLE, FREE OF BAD ODORS, AND BE UNATTRACTIVE AS A FOOD SOURCE FOR ANIMALS. IT SHOULD ALSO BE IN A GRANULAR FORM THAT IS EASILY SPREAD.
- THE APPLICATION RATE IS 34 POUNDS PER 1,000 SQUARE FEET.

CLIENT PROJECT NO: PINE GLENN FOTH PROJECT NO: 21S100.00

DESIGNED BY: KRM CHECKED BY: TFS DRAWN BY:

MAINTENANCE: BARE SPOTS OR LOCATIONS OF EROSION SHOULD BE RE-SEEDED AT NO ADDITIONAL COST TO THE CITY.

MLH

NO DATE BY

REVISION DESCRIPTION

STORMWATER POLLUTION PREVENTION PLAN (SWPPP)

Also known as an Erosion and Sediment Control Plan (ESCP)

STORMWATER POLLUTION PREVENTION PLAN (SWPPP)

Also known as an Erosion and Sediment Control Plan (ESCP)

APPROVED BY	:		
I HEREBY CERTIFY T REPORT WAS RULL SUPERVISION AND PROFESSION AND HIG STATE OF MENNESO	HAT I AM A DE	N SPECIFICATION OF THE CONTROL OF T	RECT
SIGNATURE THEOBORE F. STYPED OR PRINTED NA	SEPHIPARO!	7113	
1			_

☆ Foth

PINE GLENN STREET AND UTILITY IMPROVEMENTS


STURGIS, SOUTH DAKOTA

CIVIL STANDARDS STORMWATER POLLUTION PREVENTION PLAN

G0.04

CAD FILE: c:\pw_workdir\pw_je\mlh2\d0536124\21s100.00-stormwater pollution prevention plan.dwg

CAD DATE: 5/2/2022



TYPICAL FINISHED SECTION

* VARIES: REFER TO CROSS SECTIONS FOR DITCH AND SIDE SLOPES

APPROVED BY:

HEREBY CRIPTITE THAN THAN PARK SPECIFICATION OR REPORT WAS IN A MADE TO THE STORY WAS IN A MADE TO THE STATE OF THE STATE

 CLIENT PROJECT NO:
 PINE GLENN
 FOTH PROJECT NO:
 215100.00

 DESIGNED BY:
 KRM
 CHECKED BY:
 TFS
 DRAWN BY:
 MLH

 LETTING DATE:
 CAD DATE:
 5/2/2022
 8:25:39 AM





PINE GLENN STREET AND UTILITY IMPROVEMENTS

STURGIS, SOUTH DAKOTA

TYPICAL SECTION

SHEET NO.





GENERAL NOTES

- CONTRACTOR SHALL SUBMIT TRAFFIC CONTROL PLAN 2 WEEKS PRIOR TO START OF CONSTRUCTION. PLAN SHALL MEET THE SOUTH DAKOTA MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (SDMUTCD).
- THE SUBMITTED TRAFFIC CONTROL PLAN SHALL IDENTIFY SIDEWALK AND TRAIL CLOSURE SIGNS AND BARRICADES.
- 3. MAINTAIN EMERGENCY ACCESS AT ALL TIMES.
- CONTRACTOR RESPONSIBLE FOR RESTORING ANY DAMAGES TO SITE ACCESS ROUTES.
- CONTRACTOR SHALL PROVIDE ACCESS TO RESIDENCES AT THE END OF EACH WORKING DAY.
- CONTRACTOR SHALL REQUEST "NO PARKING" SIGNS FROM THE CITY OF STURGIS TRAFFIC DEPARTMENT NO LESS THAN 5 BUSINESS DAYS PRIOR TO ENFORCEMENT.
- CONTRACTOR SHALL PROVIDE 12-24 HOUR NOTICE PRIOR TO TEMPORARY DRIVEWAY CLOSURE.

LEGEND

— — — DETOUR ROUTE



ROAD CLOSED TO THRU

TRAFFIC

CONSTRUCTION HAUL ROUTE

TRAFFIC REQUIREMENTS FIGURE

NOT TO SCALE

 CLIENT PROJECT NO:
 PINE GLENN
 FOTH PROJECT NO:
 21S100.00

 DESIGNED BY:
 KRM
 CHECKED BY:
 TFS
 DRAWN BY:
 MLH

 LETTING DATE:
 CAD DATE:
 5/2/2022
 8:25:51 AM



PINE GLENN STREET AND UTILITY IMPROVEMENTS


STURGIS, SOUTH DAKOTA


TRAFFIC CONTROL


BORE F. SCHWIDTES


APPROVED BY:


C1.01




































NOTE: CUSTOMERS ON PINE GLENN WILL BE SWITCHED FROM PRV PRESSURE TO HIGH PRESSURE. RAISING PRESSURE BY 22 PSI APPROXIMATELY.



APPROVED BY:

I HEREBY CERTIFY THAT THE PLAN SPECIFICATION, OR REPORT TWO SPECIFICATION, OR REPORT WAS SPECIFICATION, OR THE STATE OF THE STATE OF THE STATE OF THE SCHOOL THE

Foth

PINE GLENN STREET AND UTILITY IMPROVEMENTS

MEADOW DR / DOLAN CREEK RD WATER MAIN PLAN PROFILE

C1.13